

PROTECTGUARD COLOR - 9850 - 9851

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : PROTECTGUARD COLOR
Product code : 9850 - 9851.
UFI : 6N8V-30NJ-N003-UT8P

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protection and decoration products Concrete

1.3. Details of the supplier of the safety data sheet

Registered company name : GUARD INDUSTRIE S.A.S..
Address : 7 Rue Gutenberg.93100.Montreuil.France.
Telephone : 0155861760. Fax : 0148581689.
info@guardindustrie.com
www.guardindustrie.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

Signal Word :

WARNING

Product identifiers :

613-335-00-8

4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3-ONE

613-088-00-6

1,2-BENZISOTHIAZOL-3(2H)-ONE

Additional labeling :

Hazard statements :

H317

May cause an allergic skin reaction.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P272

Contaminated work clothing should not be allowed out of the workplace.

P273

Avoid release to the environment.

PROTECTGUARD COLOR - 9850 - 9851

P280	Wear eye protection.
Precautionary statements - Response :	
P302 + P352	IF ON SKIN: Wash with plenty of water/soap.
P321	In case of visiting a doctor, show the MSDS.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Precautionary statements - Disposal :	
P501	Dispose of contents/container referring to the local regulation.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contains substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 603-052-00-8 CAS: 5131-66-8 EC: 225-878-4 3-BUTOXYPROPAN-2-OL	GHS07 Wng Eye Irrit. 2, H319 Skin Irrit. 2, H315		
CAS: 35435-21-3 EC: 252-558-3 TRIETHOXY(2,4,4-TRIMETHYLPENTYL)SILANE	Aquatic Chronic 3, H412		
INDEX: 613-335-00-8 CAS: 64359-81-5 EC: 264-843-8 4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3-ONE	GHS06, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Corr. 1, H314 Skin Sens. 1A, H317 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH:071		0 \geq x % < 0.03
INDEX: 613-333-00-7 CAS: 13463-41-7 EC: 236-671-3 PYRITHIONE ZINC	GHS08, GHS06, GHS05, GHS09 Dgr Repr. 1B, H360D Acute Tox. 2, H330 Acute Tox. 3, H301 STOT RE 1, H372 Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 1000 Aquatic Chronic 1, H410 M Chronic = 10	[2]	0 \geq x % < 0.02



PROTECTGUARD COLOR - 9850 - 9851

INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS05, GHS07, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1		0 >= x % < 0.02
INDEX: 616-212-00-7 CAS: 55406-53-6 EC: 259-627-5 3-IODO-2-PROPYNYL BUTYLCARBAMATE	GHS06, GHS08, GHS05, GHS09 Dgr Acute Tox. 3, H331 Acute Tox. 4, H302 STOT RE 1, H372 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1	[1]	0 >= x % < 0.02

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 613-335-00-8 CAS: 64359-81-5 EC: 264-843-8 4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3-ONE	Skin Corr. 1: H314 C>= 5% Skin Irrit. 2: H315 0.025% <= C < 5% Eye Dam. 1: H318 C>= 3% Eye Irrit. 2: H319 0.025% <= C < 3% Skin Sens. 1A: H317 C>= 0.0015%	inhalation: ATE = 0.16 mg/l 4h (dust/mist) oral: ATE = 567 mg/kg BW
INDEX: 613-333-00-7 CAS: 13463-41-7 EC: 236-671-3 PYRITHIONE ZINC		inhalation: ATE = 0.14 mg/l 4h (dust/mist) oral: ATE = 221 mg/kg BW
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1: H317 C>= 0.05%	

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

Following inhalation of aerosol or mist : move victims into fresh air. If symptoms persist, consult a physician for treatment.

In the event of splashes or contact with eyes :

Remove contact lenses if it is easy.

Wash thoroughly with water during 15 minutes. Consult a doctor if there is any trouble.

Refer the subject to an ophthalmologist, especially if there is redness, pain or visual discomfort.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.



PROTECTGUARD COLOR - 9850 - 9851

In the event of an allergic reaction, seek medical attention.

Wash with water and soap. if any sign/symptom develops seek for medical assistance.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.



PROTECTGUARD COLOR - 9850 - 9851

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Storage temperature : between 5 and 25°C.
keep away from direct solar light.
Maximum storage : 12 months.
N/A

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
55406-53-6		0.005 ppm 0.058 mg/m ³		2 (I)

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

TRIETHOXY(2,4,4-TRIMETHYLPENTYL)SILANE (CAS: 35435-21-3)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
12 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
84 mg of substance/m³

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term local effects.
84 mg of substance/m³

Final use:

Exposure method:
Potential health effects:
DNEL :

Man exposed via the environment.

Ingestion.
Short term systemic effects.
7.5 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Ingestion.
Long term systemic effects.
1.25 mg/kg body weight/day

Exposure method:
Potential health effects:

Dermal contact.
Short term systemic effects.



PROTECTGUARD COLOR - 9850 - 9851

DNEL :	43 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	7 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	107.2 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Short term local effects.
DNEL :	107.2 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	17.9 mg of substance/m3
3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)	
Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	44 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	270.5 mg of substance/m3
Final use:	Consumers.
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	8.75 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	16 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	33.8 mg of substance/m3

Predicted no effect concentration (PNEC):

TRIETHOXY(2,4,4-TRIMETHYLPENTYL)SILANE (CAS: 35435-21-3)	
Environmental compartment:	Soil.
PNEC :	1020 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.64 mg/l
Environmental compartment:	Sea water.
PNEC :	0.064 mg/l
Environmental compartment:	Intermittent waste water.

PROTECTGUARD COLOR - 9850 - 9851

PNEC :	1 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 5090 mg/kg
Environmental compartment: PNEC :	Marine sediment. 509 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l
Environmental compartment: PNEC :	Salt water predators (oral). 10 g/kg
3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)	
Environmental compartment: PNEC :	Soil. 0.16 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.525 mg/l
Environmental compartment: PNEC :	Sea water. 0.0525 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 5.25 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 2.36 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.236 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

PROTECTGUARD COLOR - 9850 - 9851

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Particle filter according to standard EN143 :

- P3 (White)

N/A

In case of use inside or in an area that is not correctly ventilated, use an ABEK-filter mask or a respiratory apparatus of protection autonomus insulator.

Follow the instructions of use including the maximum time of use of the devices.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Fluid liquid.

Colour

Unspecified

Odour

Odour threshold : Not stated.

Characteristic

Melting point

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not specified.

Decomposition temperature

Decomposition point/decomposition range : Not specified.

pH

pH : 8.50 +/-0.5.

Slightly basic.

pH (aqueous solution) : Not stated.



PROTECTGUARD COLOR - 9850 - 9851

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Soluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : = 1

Relative vapour density

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

Keep away from :

- acids

- strong bases

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity :

PYRITHIONE ZINC (CAS: 13463-41-7)

Oral route : LD50 = 221 mg/kg

Inhalation route (Dusts/mist) : LC50 = 0.14 mg/l



PROTECTGUARD COLOR - 9850 - 9851

Duration of exposure : 4 h

4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3-ONE (CAS: 64359-81-5)

Oral route : LD50 = 567 mg/kg

Inhalation route (Dusts/mist) : LC50 = 0.16 mg/l
Duration of exposure : 4 h

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

TRIETHOXY(2,4,4-TRIMETHYLPENTYL)SILANE (CAS: 35435-21-3)

Fish toxicity : LC50 <= 100 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 <= 100 mg/l

Algae toxicity : ECr50 <= 100 mg/l

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

TRIETHOXY(2,4,4-TRIMETHYLPENTYL)SILANE (CAS: 35435-21-3)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.



PROTECTGUARD COLOR - 9850 - 9851

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.



PROTECTGUARD COLOR - 9850 - 9851

Wording of the phrases mentioned in section 3 :

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE : Acute Toxicity Estimate
BW : Body Weight
DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
CMR: Carcinogenic, mutagenic or reprotoxic.
UFI : Unique formulation identifier.
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)
AEV : Average Exposure Value.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS07 : Exclamation mark
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.